




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>G09G 3/20</b>		A1	(11) International Publication Number: <b>WO 98/10405</b>
			(43) International Publication Date: 12 March 1998 (12.03.98)
(21) International Application Number: PCT/US97/15100 (22) International Filing Date: 27 August 1997 (27.08.97) (30) Priority Data: 08/707,156                      3 September 1996 (03.09.96)      US (71) Applicant: UNITED TECHNOLOGIES AUTOMOTIVE, INC. [US/US]; 5200 Auto Club Drive, Dearborn, MI 48126 (US). (72) Inventors: PALALAU, Silviu; 1445 Holland, Birmingham, MI 48009 (US). ROGERS, William; 10 Jacqueline Circle, Suffield, CT 06078 (US). TANSKI, William; 140 Hurlburt Street, Glastonbury, CT 06033 (US). (74) Agents: OLDS, Theodore, W. et al.; Howard & Howard Attorneys, P.C., Suite 101, 1400 North Woodward Avenue, Bloomfield Hills, MI 48304 (US).			(81) Designated States: CA, JP, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  <b>Published</b> <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: METHOD OF CONTROLLING DISPLAY IMAGE SHADING DEPENDING ON IMAGE RESOLUTION

## (57) Abstract

A method of controlling display image shading includes determining whether an image requires high resolution or low resolution shading techniques. When high resolution is required, a frame modulation technique is used. When low resolution is required, a spatial dithering technique is used. This invention also includes partitioning a display into various portions where each portion may require high or low resolution. In such instances, a high resolution technique is used for portions of the display and a low resolution technique is used for other portions of the display as needed.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

**METHOD OF CONTROLLING DISPLAY IMAGE SHADING DEPENDING ON IMAGE RESOLUTION****BACKGROUND OF THE INVENTION**

5

This invention relates to a method of controlling visual display image shading. More particularly, this invention relates to a method of choosing between alternative modes of image shading control depending on the level of resolution required for a particular visual display.

10

Various techniques are used for generating displays on electronic visual display panels. Some current techniques are more complex than others. The more complex techniques typically require more of a computer's memory and may result in higher energy usage within a given system. There is a need for improved utilization of various image shading control techniques, especially in circumstances where computer memory may be limited or power conservation is important.

15

This invention is a method of utilizing one or more image shading control techniques depending on the type of information to be displayed. More specifically, this invention is a method of choosing between image shading control techniques depending on whether a generated display requires high resolution or low resolution graphics.

20

**SUMMARY OF THE INVENTION**

25

In general terms, this invention is a method of controlling display image shading in an electrical visual display system having a display screen. The method includes several basic steps. First, two display types are defined; a first display type that requires high resolution and a second display type that requires low resolution. A determination is made whether an intended visual display is of the first display type or the second display type. When the intended display is a first display type, the display is generated on the display screen using a first image shading technique. When the intended display is a

30

second display type, the display is generated on the display screen using a second image shading technique. In the preferred embodiment, when a display requires high resolution, frame modulation is the preferred technique of image shading control. In the preferred embodiment, when the display requires low resolution, the preferred image shading technique is spatial dithering.

The various features and advantages of this invention will become apparent to those skilled in the art from the following detailed description of the presently preferred embodiment. The drawings that accompany the detailed description can be described as follows.

#### **BRIEF DESCRIPTION OF THE DRAWINGS**

Figure 1 is a schematic illustration of a visual display system.

Figure 2 is a flow chart diagram illustrating the methodology of this invention.

#### **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT**

Figure 1 schematically illustrates a visual display system including a computer memory and data processing module 4 and a video controller 6. Information from the computer memory and data processing module 4 is utilized by the video controller 6 to control a visual display displayed on a display screen 8. In the preferred embodiment, the display screen 8 is a flat panel display adapted to provide an electroluminescent display or a liquid crystal display, for example. The video controller 6 is also electrically coupled with various other input devices for receiving and processing information that may be used to modify or generate a display on the display screen 8. Given this specification, one skilled in the art can select from among commercially available microprocessors or develop specific circuitry to realize the data processing module 4 and the controller 6. Similarly, given this specification, one skilled in the art can develop specific code for

programming the controller 6 and module 4 for performing the functions associated with this invention.

Figure 2 contains a flow chart 10 that illustrates the methodology of this invention. This invention optimizes the use of gray shades and colors in flat panel displays by choosing between at least two types of techniques for controlling image shading depending on whether the image requires high resolution or low resolution. In the preferred embodiment, when high resolution is required, a frame modulation technique is utilized. Frame modulation provides high resolution but limited numbers of shades. When low resolution is sufficient, spatial dithering techniques preferably are used. Spatial dithering provides a larger number of shades or colors but cannot yield high resolution. The video controller 6 determines which technique to use based upon the resolution required for a particular display or portion of a display.

In Figure 2 an intended display is formulated at step 12. The intended display may include a variety of types of graphics. For example, if the intended display is a map, there would be graphical illustrations of roads or topography and overlying textual descriptions of roads and locations, for example. When formulating an intended display, the level of resolution that is required for a satisfactory display is determined at the step 14. When high resolution is required, such as for textual displays, a high resolution coefficient is assigned at 16. When low resolution is sufficient, a low resolution coefficient is assigned to a given display at 18. The steps 12 through 18 preferably are accomplished by the memory and data processing module 4 when formulating a databank or set of displays that will be generated on the display screen 8.

The video controller 6 defines high and low resolution display types at 20 depending on the contents of a particular display. In some instances, an entire display will be of one type or the other. In other words, some displays will require high resolution throughout the entire display, while others may require only low resolution throughout the entire display. This invention is not

limited to displays that require high or low resolution across an entire display. Some displays, such as the map example mentioned above, will be able to be generated using high resolution for portions of the display and low resolution for other portions. This invention includes utilizing separate image shading techniques for the various portions of such a display.

The video controller 6 determines the type of display at 22. A decision is made at 24 whether the display requires high resolution image shading. If it requires high resolution, then the display is generated using a frame modulation technique at 26. Developing specific circuitry or software for accomplishing a frame modulation technique can be developed by those skilled in the art and, therefore, need not be further described in this specification.

When low resolution should be used, the video controller 6 generates the display using a spatial dithering technique at 28. Developing specific circuitry or software for accomplishing a spatial dithering technique is within the scope of those skilled in the art and, therefore, need not be further described in this specification.

In those circumstances where a display requires high resolution for some portions of the display but low resolution for other portions, the video controller generates the display using frame modulation techniques and spatial dithering techniques as needed for the various portions of the display at 30.

The above description is exemplary rather than limiting in nature. Variations and modifications to the disclosed embodiment will become apparent to those skilled in the art that do not necessarily depart from the purview and spirit of this invention. Accordingly, the legal scope accorded to this invention can only be determined by studying the following claims.

**CLAIMS**

What is claimed is:

1. A method of controlling display image shading in an electrical  
5 visual display system having a display screen, comprising the steps of:
  - (A) defining a first display type as one requiring high resolution;
  - (B) defining a second display type as one requiring low resolution;
  - (C) determining whether an intended visual display is a first display  
type or a second display type;
  - 10 (D) generating the intended display on the display screen using a  
first mode of image shading when the intended display is a first display type  
display; and
  - (E) generating the intended display on the display screen using a  
second mode of image shading when the intended display is a second display  
15 type display.
2. The method of claim 1, wherein step (C) is performed by  
determining whether an entire intended display is a first or second display type  
display.  
20
3. The method of claim 1, further comprising partitioning the  
intended display into portions and wherein step (C) is performed by  
determining whether each portion is a first or second display type display,  
respectively.  
25
4. The method of claim 3, wherein steps (D) and (E) are  
performed with respect to each display portion separately.
5. The method of claim 1, wherein step (A) is performed by  
30 preselecting a high resolution coefficient value that corresponds to a display  
requiring high resolution and wherein step (B) is performed by preselecting a

low resolution coefficient value that corresponds to a display requiring low resolution.

5           6.    The method of claim 5, further comprising the step of preassigning a preselected resolution coefficient value to an intended display before performing steps (C) through (E).

10           7.    The method of claim 6, wherein step (C) is performed by determining the preassigned resolution coefficient value of the intended display.

15           8.    The method of claim 5, further comprising the steps of partitioning the intended display into a plurality of intended display components, preassigning a preselected resolution coefficient value to each intended display component before performing steps (C) through (E) and wherein step (C) is performed by determining the preassigned resolution coefficient of each intended display component.

20           9.    The method of claim 8, wherein step (D) is performed for the display components having a high resolution coefficient and wherein step (E) is performed for the display components having a low resolution coefficient.

25           10.   The method of claim 1, wherein step (D) is performed by using frame modulation.



          11.   The method of claim 1, wherein step (E) is performed by using spatial dithering.

30           12.   The method of claim 1, further comprising partitioning the intended display into a plurality of display portions wherein each display portion is either a first or second display type and wherein steps (D) and (E)



are simultaneously performed when at least one of the plurality of display portions is a first display type and at least one other display portion is a second display type and the one and one other display portions are simultaneously displayed on the display screen.

1/1

Fig-1Fig-2

# INTERNATIONAL SEARCH REPORT

Int. Application No  
PCT/US 97/15100

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 6 G09G3/20

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G09G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 673 012 A (CANON INFORMATION SYSTEMS RESEARCH AUSTRALIA PTY LTD.) 20 September 1995	1,2,11
A	see Abstract see page 3, line 11 - page 5, line 3; figures 1-7 see page 8, line 36 - line 41 see page 9, line 11 - line 30 see page 9, line 48 - page 10, line 11	3,12
X	US 5 245 328 A (GARRETT) 14 September 1993  see Abstract see column 4, line 55 - column 6, line 2; figures 1-4 see column 9, line 15 - line 36; figure 17 --- -/--	1,2,10, 11

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "A" document member of the same patent family

Date of the actual completion of the international search

19 December 1997

Date of mailing of the international search report

02/01/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280-HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Corsi, F

# INTERNATIONAL SEARCH REPORT

In. Application No  
PCT/US 97/15100

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 421 772 A (CANON K.K.) 10 April 1991 see Abstract see column 2, line 25 - column 3, line 23; figure 10 see column 5, line 24 - column 6, line 12; figures 1,2	1,2
A	EP 0 570 906 A (CANON K.K.) 24 November 1993 see Abstract see column 13, line 21 - column 15, line 7; figures 2,12-15	3,4,11, 12

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 97/15100

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 673012 A	20-09-95	AU 679320 B	26-06-97
		AU 1476395 A	26-10-95
		JP 8278768 A	22-10-96
		AU 676418 B	06-03-97
		AU 1476495 A	05-10-95
		AU 681234 B	21-08-97
		AU 1476595 A	05-10-95
		AU 679609 B	03-07-97
		AU 1477095 A	05-10-95
		CA 2144480 A	12-09-95
		CN 1111360 A	08-11-95
		EP 0671648 A	13-09-95
		EP 0673011 A	20-09-95
		JP 8050287 A	20-02-96
		JP 8069005 A	12-03-96
		JP 8201778 A	09-08-96
		AU 683131 B	30-10-97
		AU 1476795 A	05-10-95
		CA 2144479 A	12-09-95
		CN 1111361 A	08-11-95
		EP 0671650 A	13-09-95
		JP 8050288 A	20-02-96
		AU 683710 B	20-11-97
		AU 1476995 A	05-10-95
		EP 0671649 A	13-09-95
		JP 8036188 A	06-02-96
US 5245328 A	14-09-93	US 5068649 A	26-11-91
		CA 1326081 A	11-01-94
		DE 68923594 D	31-08-95
		DE 68923594 T	04-04-96
		EP 0364307 A	18-04-90
		JP 2176718 A	09-07-90
EP 421772 A	10-04-91	JP 3123386 A	27-05-91
		AT 132287 T	15-01-96
		AU 638754 B	08-07-93
		AU 6385890 A	11-04-91
		CA 2027043 A,C	07-04-91
		DE 69024448 D	08-02-96

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 97/15100

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 421772 A		DE 69024448 T	23-05-96
		ES 2081942 T	16-03-96
		KR 9402237 B	19-03-94
		KR 9402345 B	23-03-94
EP 570906 A	24-11-93	JP 5323906 A	07-12-93
		JP 5323280 A	07-12-93
		JP 5323907 A	07-12-93
		US 5613103 A	18-03-97

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☒ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**